

P- 665

General Purpose
Vinyl Coated Cloth Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Gaffer's tape
- > Holding wiring, lighting and props
- > Color coding

ADVANTAGES AND BENEFITS









- > High adhesion and tack
- > Clean removal
- > Conformable
- > Hand tearable
- > Wide variety of colors

CONSTRUCTION

Overall Grade/Function: General Purpose Gaffer's Grade
 Backing: Vinyl coated cloth
 Adhesive: Synthetic rubber



COLOR(S)

| | | | |
|---|--|--|---|
|  Black (BLK) |  Gray (GRY) |  Green (GRN) |  Red (RED) |
|  White (WHI) |  Yellow (YEL) |  Blue (BLU) |  Brown (BRN) |

STANDARD WIDTH(S)

3/4 in 24mm 48mm 72mm

STANDARD LENGTH(S)

55 yd 55m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

| | STANDARD | METRIC |
|-----------------------------|-----------------|--------------|
| Tensile Strength | 48 lbs/in width | 84.1 N/10 mm |
| Adhesion to Stainless Steel | 80 oz/in width | 8.76 N/10 mm |
| Thickness | 11.5 mils | 0.29 mm |
| Application Temperature | 45 F to 200 F | 7 C to 93 C |

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

Conforms to ASTM-D 5486M, Type IV, Class I Specifications – replaced PPP-T-60E, Type IV, Class I (Canceled 1995); A-A-1586A

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDSP-665-04/10/2006